



ISOBAR 350 CO ROCK X-HP

1020-85



Product group	110
Inner tube	Synthetic oil resistant rubber
Cover	Durable, weather and oil resistant rubber
Temperature min. °C	-40
Temperature max. °C	+121
Reinforcement	Four or six spirals of steel wire
Safety factor	1:4
Applications and characteristics	A very flexible spiral hose for the toughest applications. With the extremely durable cover and flexibility the hose is suited in applications with high demands for high flow and high pressure and is easy to assemble. MSHA approved. Exceeds the requirements of SAE 100 R13. Comes in 15,2 meter rolls. Ferrule 4400-09-xx (use only with 3/4"-1") 4400-13-xx (use only with 1 1/4"-1 1/2") 4700-04-xx (use only with 3/4" og 1") 4700-09-xx (use only with 3/4" og 1") 4700-10-xx (use only with 1 1/4" og 1 1/2")
Design	Wrapped, black
Ferrule	4200-19-xx (endast med 3/4"-1") 4700-04-xx (endast med 3/4"-1") 4700-09-xx (3/4"-1"), 4700-10-xx (1 1/4" - 1 1/2")

Material Codes



Part No.	ID mm	ID inch	OD mm	Bend rad mm	WP MPa	Weight kg/m
10208512	19	3/4"	33,3	120	34,50	1,60
10208516	25	1"	39,8	157	34,50	2,10
10208520	32	1 1/4"	51,3	210	34,50	3,60
10208524	38	1 1/2"	58,8	255	34,50	4,56