

HYDROSCAND T1112, TWIN

1032-0X



Product group	110
Inner tube	Seamless polyester elastomer
Cover	Oil, weather and abrasion resistant polyurethane
Temperature min. °C	-40
Temperature max. °C	+100
Media	Oil, Water, Welding
Reinforcement	One braid of steel wire
Safety factor	1:4
Applications and characteristics	The hose is well suitable for high pressure hydraulics. The hose is also suited for high pressure gas applications, but then needs to be pin-pricked. Due to the inner tube of polyester, the hose will retain its flexibility in cold temperatures. NOTE! Air and water max +70.
Design	Weldeed twin, black cover
Ferrule	4200-28-xx

Other



Part No.	ID mm	ID inch	OD mm	Bend rad mm	WP MPa	Weight kg/m
10320303	5	3/16"	9.7	30	36	0.24
10320404	6,50	1/4"	11.7	40	31	0.3
10320505	8	5/16"	13.2	55	25	0.38
10320606	10	3/8"	16.5	65	22,50	0.44
10320808	13	1/2"	18.8	85	19	0,58
10321010	16	5/8"	22.0	115	14	0.67
10321212	19	3/4"	25.8	145	11,50	0.89
10321616	25	1"	33	180	9,50	1.24