

P.T.F.E. ANTISTATIC

1096-11



Product group	110
Inner tube	Taped and convoluted P.T.F.E. (Teflon®)
Temperature min. °C	-40
Temperature max. °C	+205
Media	Oil
Reinforcement	One braid of stainless steel wire, SS 2330
Safety factor	1:4
Applications and characteristics	A very flexible high pressure antistatic hose due to the convoluted inner tube. The hose is suitable for most hazardous environments. Large chemical resistance range, low friction and wide temperature range. Age resistant.
Ferrule	4200-30-xx

Part No.	ID mm	ID inch	OD mm	Bend rad mm	WP MPa	Weight kg/m
10961106	10	3/8"	15.5	50	12,50	0.25
10961108	13,20	1/2"	18.7	65	10,50	0.32
10961110	16	5/8"	22.0	80	10	0.41
10961112	19,50	3/4"	26.9	100	9	0.54
10961116	25,45	1"	32.9	125	8	0.72
10961120	32	1 1/4"	39.4	150	6,40	0.82
10961124	38,15	1 1/2"	45.9	200	5,30	1.05
10961132	50,10	2"	58.4	250	3,50	1.27
10961140	64,50	2 1/2"	75.0	320	2,50	2.31
10961148	76,50	3"	88.0	380	2	2.40