

EGEFLEX 2

1102-00



Product group	100
Inner tube	Synthetic oil resistant rubber
Cover	Weather and oil resistant rubber
Temperature min. °C	-40
Temperature max. °C	+100
Media	Oil
Reinforcement	Two braids of steel wire
Safety factor	1:4
Applications and characteristics	A hose for applications with medium to high pressures. Equivalent to EN 853 2SN (41.5–8.0 MPa).
Ferrule	4200-12-xx, 4200-22-xx, 4200-23-xx

Other



Part No.	ID mm	ID inch	OD mm	Bend rad mm	WP MPa	Weight kg/m
11020003	5	3/16"	13.4	90	41,50	0.31
11020004	6,50	1/4"	15	100	40	0.33
11020005	8	5/16"	16.6	115	35	0.39
11020006	9,50	3/8"	19	130	33	0.5
11020008	13	1/2"	22.2	180	27,50	0.59
11020010	16	5/8"	25.4	200	25	0.71
11020012	19	3/4"	29.3	240	21,50	0.86
11020016	25	1"	38.1	300	16,50	1.28
11020020	32	1 1/4"	48.3	420	12,50	2.04
11020024	38	1 1/2"	54.6	500	9	2.27
11020032	51	2"	67	630	7,80	2.87
11020040	63	2 1/2"	73.3	762	6,90	3.72
11020048	76,20	3"	91.3	900	5	3.95