

EGEFLEX 2 CO

1102-14



Product group	100
Inner tube	Synthetic oil resistant rubber
Cover	Abrasion, weather and heat resistant synthetic rubber
Temperature min. °C	-40
Temperature max. °C	+100
Media	Oil
Reinforcement	Two braids of steel wire
Safety factor	1:4
Applications and characteristics	A hose for applications with medium to high pressures and a lot of external abrasion. Equivalent to EN 853 2SN. Approved by MSHA (flame resistant). The certificates refer to dimensions 3/16" – 1". Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.
Ferrule	4200-12-xx, 4200-22-xx, 4200-23-xx, 4200-32-xx

Other



Material Codes



Part No.	ID mm	ID inch	OD mm	Bend rad mm	Max length	WP MPa	Length min.	Weight kg/m
11021404	6,50	1/4"	14.4	100	-	40	-	0.31
11021405	8	5/16"	16.0	115	-	35	-	0.37
11021406	10	3/8"	18.4	130	-	33	-	0.44
11021408	13	1/2"	21.4	180	-	27,50	-	0.53
11021410	16	5/8"	24.6	200	-	25	-	0.66
11021412	19	3/4"	28.6	240	-	21,50	-	0.84
11021416	25	1"	37.1	300	-	16,50	-	1.23
11021420	32	1 1/4"	46.7	420	-	12,50	-	1,77
11021424	38	1 1/2"	54.5	500	-	9	-	2.17
11021432	51	2"	66.07	630	-	8	-	2.79
1102140430	6,50	1/4"	15,0	100	210	40	150	0,33
1102140530	8	5/16"	16,6	115	175	35	105	0,39
1102140630	10	3/8"	19.0	130	135	33	95	0,50
1102140830	13	1/2"	22,2	180	95	27,50	65	0,59