

KAPPAFLEX 2 CO SMOOTH

1104-17



Product group	100
Inner tube	Synthetic oil resistant rubber
Cover	Weather and oil resistant rubber
Temperature min. °C	-40
Temperature max. °C	+100
Media	Oil
Reinforcement	Two layers of steel wire
Safety factor	1:4
Applications and characteristics	Ozone resistant hose for applications with high pressures, well suited for marine applications. Exceeds EN 857 2SC. Part numbers ending in -30 are supplied on a reel. Joints can occur, maximum 4 lengths/bobbin and a minimum length of 5 meters per length.
Design	Smooth green and orange branding
Ferrule	4200-11-xx, 4200-23-xx, 4200-31-xx

Other



Part No.	ID mm	ID inch	OD mm	Bend rad mm	Max length	WP MPa	Length min.	Weight kg/m
11041704	6,50	1/4"	13,4	75	-	42,50	-	0,30
11041705	8	5/16"	15	85	-	40	-	0,35
11041706	10	3/8"	17,2	90	-	35	-	0,42
11041708	13	1/2"	20,4	130	-	31	-	0,52
11041710	16	5/8"	23,9	160	-	28	-	0,66
11041712	19	3/4"	27,7	195	-	28	-	0,86
11041716	25	1"	35,4	250	-	21	-	1,17
1104170430	6,50	1/4"	13,4	75	260	42,50	-	0,30
1104170630	10	3/8"	17,2	90	175	35	-	0,42
1104170830	13	1/2"	20,4	130	125	31	-	0,52
1104171230	19	3/4"	27,7	195	145	28	-	0,86