

DELTAFLX 4 CT

1115-10



Product group	110
Inner tube	Synthetic oil resistant rubber
Cover	Durable synthetic weather and heat resistant rubber
Temperature min. °C	-40
Temperature max. °C	+121
Media	Oil
Reinforcement	Four steel spirals
Safety factor	1:4
Applications and characteristics	Flexible hydraulic hose for high pressures in combination with very high pulsations. Equivalent to EN 856 4SP/4SH (1 1/4"-2"). Fire resistant (MSHA approved). The hose has a very durable cover.
Design	Wrapped, yellow-grey label
Ferrule	4200-19-xx (använd endast med 3/8"-1", ingen skalning), 4200-20-xx (använd endast med 1 1/4"-2", ingen skalning), 4700-04-xx (använd endast med 3/4"-2", ingen skalning), 4700-09-xx (använd endast med 3/4"-2", utvändig skalning), 4200-25-xx (använd endast med 3/6"-1" ingen skalning)

Other



Material Codes



Part No.	ID mm	ID inch	OD mm	Bend rad mm	WP MPa	Weight kg/m
11151006	10	3/8"	21.4	130	44,50	0.78
11151008	13	1/2"	24.6	180	42,50	0.93
11151010	16	5/8"	28.2	225	39	1.17
11151012	19	3/4"	32.2	280	35	1.48
11151016	25	1"	39.7	340	32	2.02
11151020	32	1 1/4"	45.5	460	34,50	2.46
11151024	38	1 1/2"	53.5	560	29	3.35
11151032	51	2"	68.1	700	25	4.55