

## WARECOOLER, INDUSTRIAL COOLING HOSE

1402-30



<b>Product group</b>	140
<b>Inner tube</b>	EPDM
<b>Cover</b>	EPDM rubber with a ceramic fibre cord
<b>Temperature min. °C</b>	-40
<b>Temperature max. °C</b>	+120
<b>Media</b>	Water
<b>Reinforcement</b>	Synthetic textile
<b>Safety factor</b>	1:3
<b>Applications and characteristics</b>	Used as a protection and cooling hose where the working temperature is high, e.g. melting furnaces and foundries. The cover cord is made of ceramic fibres, which gives the hose a good resistance towards flames. Sustains 1,100°C temporary radiation as well as glowing steel spatter. Electrical resistance: 10 <sup>6</sup> Ohm/m.
<b>Design</b>	White

Other



Part No.	ID mm	OD mm	Bend rad mm	Length m/coil	WP MPa	Weight kg/m
14023008	13	23	120	40	1	0.45
14023010	16	26	150	40	1	0.48
14023012	19	30	200	40	1	0.58
14023016	25	38	250	40	1	0.77
14023020	32	45	320	40	1	0.91
14023024	38	58	380	40	1	1.3
14023032	51	65	500	40	1	1.89
14023040	63,50	80	650	40	1	2.47
14023048	76	95	800	40	1	3.44
14023064	102	124	1000	40	1	5.12