

PVC DRAINAGE HOSE, LAY FLAT

1405-0X



Product group	141
Inner tube	PVC
Cover	PVC
Temperature min. °C	-20
Temperature max. °C	+60
Media	Water
Reinforcement	Synthetic textile
Safety factor	1:3

Applications and characteristics A wear resistant and durable drainage hose for pump applications. Can also be used as hose protection. Can be laid flat for transportation and storage. Other dimensions and pressure classes are available upon request. The working pressures mentioned below are valid at +20 C.

Other



Part No.	ID mm	OD mm	Length m/coil	WP MPa	Weight kg/m
14050012	20	23.0	100	0,70	0.14
14050016	26	29.0	100	0,70	0.17
14050020	33	35.9	100	0,70	0.20
14050024	41	42.6	100	0,50	0.21
14050032	53	54.7	100	0,50	0.27
1405003291	53	54,7	50	0,50	0,27
14050040	66	68.0	100	0,40	0.38
14050048	78	80.4	100	0,40	0.53
1405004891	78	80,4	50	0,40	0,53
14050064	104	106.5	100	0,40	0.70
1405006491	104	106,5	50	0,40	0,70
14050080	128	132.0	100	0,30	0.94
14050096	155	159.0	100	0,30	1.18
14050204	207	212.0	100	0,30	1.90
14050250	257	262.2	100	0,25	2.65