

SPIRAL SUCTION HOSE, SUPER ELASTIC PVC

1407-10



Product group 141

Inner tube PVC

Cover PVC

Temperature min. °C -25

Temperature max. °C +55

Media Water, Materials

Reinforcement PVC spiral

Safety factor 1:3

Applications and characteristics A suction hose for sewage trucks, grains and fertilizing. Pliable and flexible at low temperatures. The extra hard PVC spiral gives an extraordinary protection against external abrasion.

Other



Part No.	ID mm	OD mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
14071016	25	33.8	100	90	50	0,70	0.5
14071020	32	40.8	130	90	50	0,60	0.6
14071024	38	46.8	150	90	50	0,60	0.7
14071032	50	61	200	90	50	0,50	1.05
14071040	63	74	250	90	50	0,45	1.39
14071048	76	89	300	90	30	0,40	1.7
14071148	76	89	300	90	50	0,40	1.7
14071051	80	93	320	90	30	0,35	1.85
14071056	89	102.4	360	90	30	0,35	2.25
14071064	102	116.6	400	90	30	0,35	2.70
14071164	102	116.6	400	90	50	0,35	2.70
14071069	110	125	440	90	20	0,35	3.1
14071077	120	135.6	480	90	20	0,25	3.6
14071080	127	143.6	510	90	20	0,25	3.9
14071096	152	170	610	90	20	0,20	5
14071160	160	180	640	90	20	0,20	5.6
14071200	200	226	800	90	10	0,15	10
14071254	254	283	1000	90	10	0,15	13.5