

AQUASEWER, FLUSHING HOSE 250 BAR

1415-XX



Product group	140
Inner tube	Synthetic rubber (SBR)
Cover	Abrasion and weather resistant rubber (NR/NBR)
Temperature min. °C	-35
Temperature max. °C	+80
Media	Water
Reinforcement	Two layers of textile
Safety factor	1:2,5
Applications and characteristics	A hose for high pressure flushing of sewers and swage systems. Its abrasion proof cover and textile reinforcement make it flexible and very easy to handle. Pre-assembled with an internal, alternative external, and external thread (BSP). Delivered with Pressure Test Certificate.
Design	Smooth, black

Other



Part No.	ID mm	OD mm	Bend rad mm	Length m/coil	WP MPa	Thread	Weight kg/m
14150608	13	25.0	70	60	25	INT-EXT	0.46
1415060890	13	25.0	70	60	25	EXT-EXT	0.46
14150808	13	25.0	70	80	25	INT-EXT	0.46
1415080890	13	25.0	70	80	25	EXT-EXT	0.46
14151208	13	25.0	70	120	25	INT-EXT	0.46
1415120890	13	25.0	70	120	25	EXT-EXT	0.46
14151216	25	39.0	110	120	25	INT-EXT	0.86
1415121690	25	39.0	110	120	25	EXT-EXT	0.86
14151516	25	39.0	110	150	25	INT-EXT	0.86
1415151690	25	39.0	110	150	25	EXT-EXT	0.86
1415161690	25	39.0	110	160	25	EXT-EXT	0.86
14151220	32	48.0	150	120	25	INT-EXT	1.27
14151520	32	48.0	150	150	25	INT-EXT	1.27
14151820	32	48.0	150	180	25	INT-EXT	1.27