

HYDROAIR, AIR PRESSURE HOSE, 15 BAR

1420-00



Product group	142
Inner tube	Synthetic rubber (SBR)
Cover	Abrasion resistant synthetic rubber (SBR)
Temperature min. °C	-25
Temperature max. °C	+70
Media	Air pressure
Reinforcement	Synthetic textile
Safety factor	1:3
Applications and characteristics	This air pressure hose is suitable for most applications, tools, air pressure units and rock drills etc. Used in engineering, mining and construction industries. Sustains oil mist.

Other



Part No.	ID mm	OD mm	Bend rad mm	Length m/coil	WP MPa	Weight kg/m
14200004	6	12	50	40	1,50	0.13
14200005	8	14	65	40	1,50	0.19
14200006	10	17	80	40	1,50	0.22
14200008	13	22	105	40	1,50	0.32
14200010	16	25	130	40	1,50	0.49
14200012	19	28	150	40	1,50	0.57
14200016	25	36	200	40	1,50	0.79
14200020	32	44	320	40	1,50	0.94
14200024	38	52	380	40	1,50	1.42
14200032	51	65	500	40	1,50	1.98
14200040	63	78	650	40	1,50	2.42
14200048	76	90	750	40	1,50	2.8
14200064	102	115	1000	40	1,50	3.55