

FRØY CORRUGATED MARINE EXHAUST HOSE

1434-60



Product group	140
Inner tube	NBR
Cover	Flame resistant and weatherproof antistatic synteti rubber
Temperature min. °C	-30
Temperature max. °C	+100
Media	Oil
Reinforcement	Syntetic cord and steel spiral
Safety factor	1:5
Applications and characteristics	Marine exhaust hose, also for gasoline and diesel. Prodused according to Nordic boat standard 1990 MC-8 and MC-9. EN ISO 7840 A1.
Design	Corrugated, black

Other



Material Codes



Part No.	ID mm	OD mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
14346016	25	35	100	80	40	0,30	0.77
14346020	32	42	130	80	40	0,30	0.94
14346024	38	48	160	80	40	0,30	1.09
14346028	45	55	180	80	40	0,30	1.26
14346032	50	60	200	80	40	0,30	1.41
14346035	55	65	220	80	40	0,30	1.53
14346040	63,50	73.5	255	80	40	0,30	1.85
14346048	76	86	300	80	20	0,30	2.29
14346056	90	100	460	80	20	0,30	2.67
14346064	102	113	410	80	20	0,30	3.24
14346080	125	139	500	80	20	0,30	5.02