

RAGOIL, FUEL HOSE

1437-00



Product group	140
Inner tube	Oil resistant rubber
Cover	Oil resistant rubber, one outer braid of steel
Temperature min. °C	-40
Temperature max. °C	+80
Media	Oil
Safety factor	1:2,5
Applications and characteristics	The hose is designed for oil leaded, unleaded gasoline and diesel pipes, and also to be used as a lubrication oil hose. It does not sustain E85 and RME. For fuel fittings, see chapter 5:0.
Design	Metal braided

Other



Part No.	ID mm	OD mm	Bend rad mm	Length m/coil	WP MPa	Weight kg/m
14370002	3,50	8.5 (NW: 2)	25	20	3,20	0.13
14370003	4,50	9.5 (NW: 3)	25	20	3	0.15
14370004	5,50	10.5 (NW: 4)	25	20	3	0.19
14370006	7,50	12.5 (NW: 6)	30	20	2,40	0.22
14370008	9,50	15 (NW: 8)	40	20	2	0.25
14370010	11	17.5 (NW: 10)	45	20	2	0.29
14370013	14	21.5 (NW: 13)	50	20	1,80	0.37
14370016	17,50	26 (NW: 16)	70	20	1,40	0.48
14370020	20,50	32 (NW: 20)	90	20	1,40	0.55