

HYDROSCAND MULTIFLEX SUCTION AND PRESSURE

1438-60



Product group	140
Inner tube	Smooth nitrilerubber
Cover	Durable, oil and ozon resistant corrugated CR rubber
Temperature min. °C	-30
Temperature max. °C	+120
Media	Oil
Reinforcement	Textile and steel spiral
Applications and characteristics	Suction and pressure hose for oil, diesel fuel and gasoline, with a maximum of 50% aromatic content. The hose is corrugated antistatic wire which is a very good solution where there is a need for a flexible hose.
Design	Corrugated, black with orange stripe

Other



Part No.	ID mm	OD mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
14386008	13	22	60	50	20	0,50	0.32
14386010	16	24	65	50	20	0,50	0.39
14386012	19	27	70	50	20	0,50	0.425
14386014	22	31	75	50	20	0,50	0.49
14386016	25	34	90	50	20	0,50	0.55
14386018	28	35	100	50	20	0,50	0.59
14386020	32	41	110	50	20	0,50	0.65
14386022	35	43	125	50	20	0,50	0.7
14386024	38	46	135	50	20	0,50	0.74
14386026	42	50	140	50	20	0,50	0.8
14386030	45	53	145	50	20	0,50	0.86
14386032	51	60	170	80	20	0,50	1
14386036	58	66	200	50	20	0,50	1.38
14386040	63,50	72	260	50	20	0,50	1.52
14386044	70	79	300	50	20	0,50	1.75
14386048	76	85	370	50	20	0,50	1.99
14386064	102	114	520	50	20	0,50	2.72
14386080	127	144	680	50	20	0,50	4.08