

## YELLOW PYTHON, 30 BAR

1456-00



|                                         |                                                                                                                                                                                                                               |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product group</b>                    | 140                                                                                                                                                                                                                           |
| <b>Inner tube</b>                       | Heat resistant rubber (EPDM)                                                                                                                                                                                                  |
| <b>Cover</b>                            | Heat and ozone resistant rubber (EPDM)                                                                                                                                                                                        |
| <b>Temperature min. °C</b>              | -40                                                                                                                                                                                                                           |
| <b>Temperature max. °C</b>              | +110                                                                                                                                                                                                                          |
| <b>Media</b>                            | Chemicals, Water, Air pressure                                                                                                                                                                                                |
| <b>Reinforcement</b>                    | Synthetic textile                                                                                                                                                                                                             |
| <b>Safety factor</b>                    | 1:3                                                                                                                                                                                                                           |
| <b>Applications and characteristics</b> | A very flexible hose with a wide temperature range. Well suited for air and hot and cold water. It is resistant towards lighter chemicals. It has good ozone resistance and will temporarily sustain temperatures up to 130 C |
| <b>Design</b>                           | Smooth, yellow. Wrapped from 25 mm                                                                                                                                                                                            |

### Other



| Part No. | ID mm | OD mm | Bend rad mm | Length m/coil | WP MPa | Weight kg/m |
|----------|-------|-------|-------------|---------------|--------|-------------|
| 14560004 | 6     | 14    | 40          | 40            | 3      | 0.19        |
| 14560006 | 10    | 20    | 60          | 40            | 3      | 0.35        |
| 14560008 | 13    | 23    | 80          | 40            | 3      | 0.41        |
| 14560010 | 16    | 27    | 100         | 40            | 3      | 0.55        |
| 14560012 | 19    | 30    | 110         | 40            | 3      | 0.63        |
| 14560016 | 25    | 37    | 150         | 40            | 3      | 0.88        |
| 14560020 | 32    | 44    | 320         | 40            | 3      | 0.95        |
| 14560024 | 38    | 51    | 380         | 40            | 3      | 1.35        |
| 14560032 | 50    | 66    | 500         | 40            | 3      | 1.82        |