

VACUUM HOSE, POLYURETHANE ANTISTATIC

1463-40



Product group	140
Inner tube	Polyurethane (PU)
Cover	Polyurethane (PU)
Temperature min. °C	-25
Temperature max. °C	+85
Media	Materials, Food, Ventilation
Reinforcement	PVC spiral with antistatic wire
Applications and characteristics	A hose suitable in situations when a grounded braid is needed to transport abrasive materials, mineral wool insulation and ventilation. The hose is made of polyurethane and is very flexible. Food approved.
Design	Corrugated, transparent

Other



Part No.	ID mm	Thickness mm	Bend rad mm	Vacuum pr Max%	Length m/coil	Weight kg/m
14634020	32	0.6	32	40	20	0.24
14634022	35	0.6	35	40	20	0.25
14634024	38	0.6	38	30	20	0.33
14634025	40	0.6	40	30	20	0.36
14634026	40	0.6	40	30	20	0.33
14634032	50	0.7	50	30	20	0.44
14634039	60	0.7	60	30	20	0.5
14634040	63	0.7	63	30	20	0.53
14634048	75	0.7	75	30	20	0.66
14634050	80	0.7	80	30	20	0.74
14634064	100	0.8	100	30	20	0.92
14634080	125	0.8	125	30	20	1.25
14634096	150	0.9	150	30	20	1.6