

CORRUGATED SUCTION AND PRESSURE HOSE FOR AGRICULTURE

1465-7X



Product group	140
Inner tube	Black SBR/EPDM
Cover	Black SBR
Temperature min. °C	-30
Temperature max. °C	+80
Media	Materials, Water
Reinforcement	Steel spiral and textile
Safety factor	1:3
Applications and characteristics	Suction and pressure hose for lightly abrasive materials.

Other



Part No.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
14657332	51	306	0,9	3*	0,60	1.5
14657432	51	306	0,9	4*	0,60	1.5
14657132	51	306	0,9	6*	0,60	1.5
14657038	60	360	0,9	40	0,60	1.8
14657138	60	360	0,9	6*	0,60	1.8
14657238	60	360	0,9	5*	0,60	1.8
14657148	76	456	0,9	6*	0,60	2.15
14657348	76	456	0,9	3*	0,60	2.15
14657448	76	456	0,9	4*	0,60	2.15
14657050	80	480	0,9	40	0,60	2.3
14657150	80	480	0,9	5*	0,60	2.3
14657164	102	612	0,9	5*	0,60	3.6
14657469	110	660	0,9	4*	0,60	3.7
14657369	110	660	0,9	2,65*	0,60	3.7
14657569	110	660	0,9	3*	0,60	3.7
14657180	127	762	0,8	6*	0,60	4.5
14657480	127	762	0,8	4*	0,60	4.5
14657580	127	762	0,8	5*	0,60	4.5
14657196	152	912	0,8	6*	0,60	6.3
146571964	152	912	0,8	4*	0,60	6.3
1465720338	203	1218	0,8	3.8*	0,60	10
146572033	203	1218	0,8	3*	0,60	10
146572034	203	1218	0,8	4*	0,60	10
146572035	203	1218	0,8	5*	0,60	10

Part No.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
146572036	203	1218	0,8	6*	0,60	10
14657254	254	1524	0,8	4*	0,60	18
14657255	254	1524	0,8	5*	0,60	18