

CONCRETE HOSE 85 BAR

1468-XX



Product group	140
Inner tube	Black rubber, durable
Cover	Black rubber, weather and abrasion resistant
Temperature min. °C	-40
Temperature max. °C	+70
Media	Materials
Reinforcement	Steel reinforcement
Safety factor	1:2
Applications and characteristics	Mandrel built steel reinforced concrete placement hose. Delivered in different sizes and lengths assembled with hardened vicatolic fittings. See also table to identify the various sizes of victaulic couplings.
Design	Fabric impression

Part No.	Thread
14680340	21/2" Marble Concrete. 85 Bar 3m. M/88,9mm Victaulic
14680440	21/2" Marble Concrete. 85 Bar 4m. M/88,9mm Victaulic
14680540	21/2" Marble Concrete. 85 Bar 5m. M/88,9mm Victaulic
14680640	21/2" Marble Concrete. 85 Bar 6m. M/88,9mm Victaulic
14680740	21/2" Marble Concrete. 85 Bar 7m. M/88,9mm Victaulic
14681040	21/2" Marble Concrete. 85 Bar 10m. M/88,9mm Victaulic
14681240	21/2" Marble Concrete. 85 Bar 12m. M/88,9mm Victaulic
14680348	3" Marble Concrete. 85 Bar 3m. M/97mm Victaulic
14680448	3" Marble Concrete. 85 Bar 4m. M/97mm Victaulic
14680548	3" Marble Concrete. 85 Bar 5m. M/97mm Victaulic
14680748	3" Marble Concrete. 85 Bar 7m. M/97mm Victaulic
14681048	3" Marble Concrete. 85 Bar 10m. M/97mm Victaulic
14680364	4" Marble Concrete. 85 bar 3m. M/114,3mm Victaulic
14680464	4" Marble Concrete. 85 bar 4m. M/114,3mm Victaulic
14680564	4" Marble Concrete. 85 bar 5m. M/114,3mm Victaulic
14684564	4" Marble Concrete. 85 bar 4,5m. M/114,3mm Victaulic
1468034890	80mm Marble Concrete. 85 bar 3m. M/97mm Victaulic
1468044890	80mm Marble Concrete. 85 bar 4m. M/97mm Victaulic
1468054890	80mm Marble Concrete. 85 bar 5m. M/97mm Victaulic
1468074890	80mm Marble Concrete. 85 bar 7m. M/97mm Victaulic