

EXHAUST HOSE FOR HOT AIR, NEOPREN, SINGLE COATED

1561-0X



Product group	140
Cover	Neoprene, single coated (CR)
Temperature min. °C	-35
Temperature max. °C	+135
Media	Ventilation
Reinforcement	Woven fiberglass, steel spiral
Applications and characteristics	A hose suitable for transportation of hot seams, smoke and exhaust gases. Low-weight and very flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.
Design	Slightly corrugated, black

Other



Part No.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP BAR	Weight kg/m
15610016	25	17	5.0	4	1.5	0.12
15610020	32	19	5.0	4	1.5	0.13
15610029	44	26	5.0	4	1.5	0.19
15610032	51	30	5.0	4	1.5	0.25
15610040	63	36	5.0	4	1.3	0.30
15610048	76	42	4.0	4	1.1	0.40
15610055	89	49	4.0	4	1.1	0.50
15610064	102	55	3.0	4	1.1	0.57
15610080	127	69	2.1	4	0.9	0.81
15610096	152	81	1.8	4	0.8	1.05
15610180	180	94	1.0	4	0.6	1.21
15610203	203	107	1.0	4	0.6	1.38
15610254	254	132	1.0	4	0.4	1.65
15610305	305	158	0.7	4	0.1	2.00