

POLYURETHANE HOSE M 0.7

1563-30



Product group	140
Inner tube	Polyurethane (PU)
Cover	Polyurethane (PU)
Temperature min. °C	-40
Temperature max. °C	+90
Media	Materials, Ventilation
Reinforcement	Copper-coloured steel spiral
Applications and characteristics	Powerful and flexible suction hose for transportation of materials such as gravels, cement, sand, sawdust, gasoline, oil products and food. The hose is suitable in areas such as sawmills, plastic and paper industries, wood shaving, contractor businesses. Good resistant towards solvents and good aging characteristics. It is also resistant to oil mist and microbes, and can be used in damp environments. Halogen free. (Length 10 m available on request).
Design	Corrugated, transparent, internally smooth

Other



Part No.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
15633012	20	28	80	10	0,35	0.21
15633016	25	30	80	10	0,33	0.23
15633020	32	40	71	10	0,25	0.35
15633024	38	46	66	10	0,21	0.39
15633025	40	48	66	10	0,21	0.40
15633032	51	58	52	10	0,17	0.48
15633038	55	63	44	10	0,15	0.51
15633040	63	72	37	10	0,13	0.62
15633041	65	73	37	10	0,13	0.64
15633044	70	78	37	10	0,11	0.68
15633048	76	84	29	10	0,11	0.72
15633050	80	88	29	10	0,10	0.76
15633055	90	99	22	10	0,08	0.88
15633064	102	110	22	10	0,08	0.95
15633070	110	119	22	10	0,07	1.03
15633074	115	124	22	10	0,07	1.06

Part No.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
15633076	120	129	22	10	0,07	1.12
15633080	127	135	22	10	0,07	1.18
15633140	140	149	15	10	0,06	1.38
15633096	152	161	15	10	0,06	1.48
15633160	160	170	15	10	0,06	1.74
15633165	165	175	15	10	0,04	1.78
15633170	170	180	15	10	0,04	1.80
15633175	175	185	15	10	0,04	1.85
15633180	180	190	15	10	0,04	1.90
15633203	203	214	15	10	0,04	2.30
15633220	220	230	7	10	0,03	2.52
15633228	228	240	7	10	0,03	2.63
15633254	254	264	7	10	0,03	3.02
15633305	305	315	7	10	0,03	3.22
15633318	318	330	7	10	0,03	3.38
15633350	350	360	7	10	0,01	3.60
15633400	400	410	5	10	0,01	4.45
15633450	450	460	5	10	0,01	5.06
15633500	500	510	5	10	0,01	5.70