

POLYURETHANE HOSE H 0.4

1563-50



Product group	140
Inner tube	Polyurethane (PUR)
Cover	Polyurethane (PUR)
Temperature min. °C	-40
Temperature max. °C	+90
Media	Materials
Reinforcement	Copper-coloured steel spiral
Applications and characteristics	A very powerful PU-hose for transportation of strong abrasive particles. The hose is suitable for industrial vacuum cleaning, granulates and splinters. It is also resistant to oil mist and microbes, and can be used in damp environments. Halogen free.
	Materialtykkelse: 1,4 mm
Design	Corrugated, transparent, internally smooth

Other



Part No.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
15635020	32	60	92	10	0,36	0.39
15635022	35	65	92	10	0,34	0.42
15635024	38	69	82	10	0,31	0.46
15635025	40	72	82	10	0,31	0.49
15635032	51	87	82	10	0,29	0.71
15635038	55	95	76	10	0,28	0.77
15635040	63	111	66	10	0,24	0.86
15635044	70	117	66	10	0,23	0.97
15635048	76	126	59	10	0,20	1.06
15635050	80	132	59	10	0,20	1.11
15635064	102	165	44	10	0,15	1.48
15635076	120	194	31	10	0,13	1,75
15635080	127	203	31	10	0,13	1.91
15635085	140	224	26	10	0,11	2,11
15635096	152	242	26	10	0,11	2.29
15635160	160	255	25	10	0,09	2.51
15635175	175	278	18	10	0,09	2.74
15635180	180	285	18	10	0,08	2.82
15635203	203	321	18	10	0,08	3.50

Part No.	ID mm	Bend rad mm	Vacuum pr Max%	Length m/coil	WP MPa	Weight kg/m
15635220	220	353	12	10	0,06	3.65
15635250	250	390	12	10	0,06	3.91
15635300	300	465	12	10	0,05	4,94
15635350	350	540	12	10	0,05	6.96
15635400	400	615	7	10	0,03	7.95
15635450	450	690	7	10	0,03	8.94