

COMP TEMP 305

1583-10



Product group 140

Temperature min. °C -40

Temperature max. °C +200

Media Special, Chemicals, Oil

Reinforcement AISI 316 L stainless inner spiral. Outer spiral of galvanised steel.

Applications and characteristics A hose that is made especially for transportation of hot oil and bitumen under suction or pressure. COMP HITEMP 305 is suitable when loading and unloading gas trucks, but also for fixed industrial applications. The P.T.F.E. inner tube makes the hose sleek internally with low friction as a result. All hoses are 100 % aromatically resistant, anti-static and can be used both for suction and pressure applications. Supplied in 40m coils. Vacuum = 70%

Design Black

Other



Part No.	ID mm	ID inch	Bend rad mm	Max length	Colour	WP MPa	BP MPa	Weight kg/m
15831012	20	3/4"	150	35 m	Black	1,50	7,50	1.1
15831016	25	1"	200	35 m	Black	1,50	7,50	1.2
15831020	32	1 1/4"	200	35 m	Black	1,50	7,50	1.6
15831024	40	1 1/2"	200	35 m	Black	1,50	7,50	2.0
15831032	50	2"	225	35 m	Black	1,50	7,50	2.9
15831040	65	2 1/2"	225	35 m	Black	1,50	7,50	3.8
15831048	75	3"	300	35 m	Black	1,50	7,50	4.7
15831064	100	4"	400	35 m	Black	1,50	7,50	6.9