

# COMP P.T.F.E 300

1584-11



**Product group** 140

**Temperature min. °C** -40

**Temperature max. °C** +120

**Media** Special, Chemicals, Oil

**Reinforcement** Stainless inner and outer spirals.

**Applications and characteristics** Especially made for use as a universal hose for transportation of a wide spectra of aggressive medias. The hose is suitable when loading and unloading gas trucks and railroad cars as well as within the industry in different processes. Electric continuity is attained when the two spirals are put towards the hose's fittings. In this way, static electricity is avoided. The electric resistance in an assembled hose is smaller than 10 Ohm, according to BS 5842:1980 § 6.2. On request, a Special flame resistant version can also be delivered. Supplied in 40m coils. Vacuum = 70%

**Design** Red

## Other



Part No.	ID mm	ID inch	Bend rad mm	Max length	Colour	WP MPa	Weight kg/m
15841112	20	3/4"	50	35 m	Red	1,50	0.8
15841116	25	1"	75	35 m	Red	1,50	0.9
15841120	32	1 1/4"	80	35 m	Red	1,50	1.0
15841124	40	1 1/2"	85	35 m	Red	1,50	1.4
15841132	50	2"	125	35 m	Red	1,50	2.0
15841140	65	2 1/2"	150	35 m	Red	1,50	3.2
15841148	75	3"	175	35 m	Red	1,50	3.6
15841164	100	4"	250	35 m	Red	1,50	5.0