



HS 320 COUPLING

5552-28



Product info

Now Hydroscand's own 320 coupling is in stock! The quick-release coupling replaces Cejns standard 320 coupling (not esafe) where the HS 320 coupling also has a rubber sleeve. Due to the solid construction with rubber sleeve, the clutch does not wear easily and it is non-abrasive to surrounding components. This is an affordable coupling operated with a single hand, which makes the clutch very easy to connect to other pneumatic driven devices. The coupling is suitable for workshops where there is a need for easy and quick connection and disconnection to different compressed air tools. Industries that need a simple connection for machinery and equipment powered by compressed air, benefit from this user-friendly coupling.

Manufacturer

Gromelle

Standard

Eurostandard 7,2/7,4 mm

Interchangeable with

Rectus 25/26, Tema 1600/1625, Prevost ESC07/ESC07/ESI07/Isco08, Oetiker SC C, Hansen Auto-Flo 24, Cejn 320

Temperature min. °C -20

Temperature max. °C +100

Part No.	Connection
55522812	G 1/4" IF
55522815	G 3/8" IF
55522816	G 1/2" IF
55522822	R 1/4" UF
55522825	R 3/8" UF
55522826	R 1/2" UF
55522832	Hose 6 mm
55522833	Hose 8 mm
55522835	Hose 10 mm
55522836	Hose 13 mm