

## CEJN 320 SAFETY FITTING

5C10320-2X



|                                         |                                                                                                               |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>Product info</b>                     | eSafe Safety fitting, female                                                                                  |
| <b>Product info2</b>                    | Female thread                                                                                                 |
| <b>Product group</b>                    | 524                                                                                                           |
| <b>Type</b>                             | Air                                                                                                           |
| <b>Manufacturer</b>                     | Cejn                                                                                                          |
| <b>Standard</b>                         | Eurostandard 7.6 (7.4)                                                                                        |
| <b>Connection force</b>                 | 86 N                                                                                                          |
| <b>Applications and characteristics</b> | ISO-standard 4414 and EN 983<br>Use with standard nipples (see related products)                              |
| <b>Interchangeable with</b>             | Parker Rectus 25/26, Parker Tema 1600/1625, Prevost ESC07/ERC07/ESI07/ISC08, Oetiker SC C, Hansen Auto-Flo 24 |
| <b>Temperature min. °C</b>              | -20                                                                                                           |
| <b>Temperature max. °C</b>              | +100                                                                                                          |
| <b>Min. bursting pressure</b>           | 140 bar                                                                                                       |

| Part No.    | Connection | Cejn descr. |
|-------------|------------|-------------|
| 5C103202202 | G 1/4" F   | 10 320 2202 |
| 5C103202204 | G 3/8" F   | 10 320 2204 |
| 5C103202205 | G 1/2" F   | 10 320 2205 |
| 5C103202402 | NPT 1/4" F | 10 320 2402 |
| 5C103202404 | NPT 3/8" F | 10 320 2404 |
| 5C103202405 | NPT 1/2" F | 10 320 2405 |